

## Taricnr för tullbefrielser som upphör 31 december 2017 till följd av för låg importvolym

Taricnr	DESCRIPTION
2007995081, 2007995091	Acerola puree concentrate, obtained by cooking:— of the Genus Malpighia spp.,— with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry (2)
2007995082, 2007995092	Acidified banana puree concentrate, obtained by cooking:— of the Genus Musa cavendish,— with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry (2)
2811198030	Phosphorous acid (CAS RN 10294-56-1)/phosphonic acid (CAS RN 13598-36-2) used as an ingredient for production of additives used in poly(vinyl chloride) industry (2)
2823000020	Titanium dioxide (CAS RN 13463-67-7) with a purity of 99,7 % or more and containing by weight:— not more than 0,005 % of potassium and sodium combined (expressed as elemental sodium and elemental potassium),— not more than 0,01 % of phosphorus (expressed as elemental phosphorus), for use in the metallurgy (2)
2850002050	Sodium tetrahydroborate (CAS 16940-66-2) with:— a purity by weight of 98 % or more and— not more than 10ppm iron for use as an additive in the manufacture of oxygen barrier polymer articles (2)
2907290055	Biphenyl-2,2'-diol (CAS RN 1806-29-7)
2908990040	4,5-Dihydroxynaphthalene-2,7-disulphonic acid (CAS RN 148-25-4)
2912290050	4-Isobutylbenzaldehyde (CAS RN 40150-98-9)
2914500070	16 $\alpha$ ,17 $\alpha$ -Epoxy-3 $\beta$ -hydroxypregn-5-en-20-one (CAS RN 974-23-2)
2915907075	2,2-Dimethylbutyryl chloride (CAS RN 5856-77-9)
2921430080	6-Chloro- $\alpha,\alpha,\alpha$ -trifluoro-m-toluidine (CAS RN 121-50-6)
2921490085	4-Isopropylaniline (CAS RN 99-88-7)
2922190025	Titanium bis(triethanolamine)diisopropoxide (CAS RN 36673-16-2)
2924297051	Methyl 2-amino-4-[(2,5-dichlorophenyl)amino]carbonyl]benzoate (CAS RN 59673-82-4)
2930909866	Diphenyl sulphide (CAS RN 139-66-2)
2930909883	Methyl-p-tolyl sulphone (CAS RN 3185-99-7)
2932209020	Ethyl 6'-(diethylamino)-3-oxo-3H-spiro[2-benzofuran-1,9'-xanthene]-2'-carboxylate (CAS RN 154306-60-2)
2933199085	Allyl 5-amino-4-(2-methylphenyl)-3-oxo-2,3-dihydro-1H-1-pyrazolcarbothioate (CAS RN 473799-16-5)
2933399918	6-Chloro-3-nitropyridin-2-ylamine (CAS RN 27048-04-0)
2933998018	4,4'-[(9-Butyl-9H-carbazol-3-yl)methylene]bis[N-methyl-N-phenylaniline] (CAS RN 67707-04-4)
2933998028	N-(2,3-Dihydro-2-oxo-1H-benzimidazol-5-yl)-3-hydroxynaphthalene-2-carboxamide (CAS RN 26848-40-8)
2933998043	2,3-Dihydro-1H-pyrrole[3,2,1-ij]quinoline (CAS RN 5840-01-7)

2934999014	Ethyl N-{{[1-methyl-2-{{[4-(5-oxo-4,5-dihydro-1,2,4-oxadiazol-3-yl)phenyl]amino}methyl)-1H-benzimidazol-5-yl]carbonyl}-N-pyridin-2-yl-b-alaninate (CAS RN 872728-84-2)
2934999018	3,3-bis(2-Methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0)
2934999022	7-[4-(Diethylamino)-2-ethoxyphenyl]-7-(2-methyl-1-octyl-1H-indol-3-yl) furo[3,4-b]pyridin-5(7H)-one (CAS RN 87563-89-1)
3204110070	Colourant C.I. Disperse Red 343 (CAS RN 99035-78-6) and preparations based thereon with a colourant C.I. Disperse Red 343 content of 95 % or more by weight
3204110080	Dye preparation, non-ionogenic, containing: — N-[5-(acetylamino)-4-[(2-chloro-4,6-dinitrophenyl)azo]-2-methoxyphenyl]- 2-oxo-2-(phenylmethoxy)ethyl-β-alanine (CAS RN 159010-67-0) — N-[4-[(2-cyano-4-nitrophenyl)azo]phenyl]-N-methyl-2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethyl-β-alanine (CAS RN 170222-39-6) and — N-[2-chloro-4-[(4-nitrophenyl)azo]phenyl]-2-[2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethoxy]-2-oxoethyl-β-alanine (CAS RN 371921-34-5) 
3204120020	Dye preparation, anionic, containing by weight 75 % or more of disodium-7-((4-chloro-6-(dodecylamino)-1,3,5-triazin-2-yl)amino)-4-hydroxy-3-((4-((4-sulfophenyl)azo)phenyl)azo)-2-naphthalenesulfonate (CAS RN 145703-76-0)
3204120030	Acid dye preparation, anionic, containing: — lithium-amino-4-(4-tert-butylanilino)anthraquinone-2-sulfonate (CAS RN 125328-86-1), — C.I. Acid Green 25 (CAS RN 4403-90-1) and — C.I. Acid Blue 80 (CAS RN 4474-24-2) 
3204130020	(2,2'-(3,3'-Dioxidobiphenyl-4,4'-diyldiazo)bis(6-(4-(3-(diethylamino)propylamino)-6-(3-(diethylammonio)propylamino)-1,3,5-triazin-2-ylamino)-3-sulfonato-1-naphtholato))dicopper(II) acetate lactate (CAS RN 159604-94-1)
3204130030	Colourant C.I. Basic Blue 7 (CAS RN 2390-60-5) and preparations based thereon with a colourant C.I. Basic Blue 7 content of 50 % or more by weight
3204190085	Colourant C.I. Solvent Red HPR (CAS RN 75198-96-8) and preparations based thereon with a colourant C.I. Solvent Red HPR content of 95 % or more by weight
3215199020	Ink: — consisting of a polyester polymer and a dispersion of silver (CAS RN 7440-22-4) and silver chloride (CAS RN 7783-90-6) in methyl propyl ketone (CAS RN 107-87-9), — with a total solid content by weight of 55 % or more, but not more than 57 %, and — with a specific gravity of 1,40 g/cm <sup>3</sup> or more, but not more than 1,60 g/cm <sup>3</sup> , used to imprint electrodes (2) 
3802900011	Soda flux calcinated diatomaceous earth, acid washed, for use as a filter aid in the manufacture of pharmaceutical and/or biochemical products (2) 
3808931510	Preparation based on a concentrate containing by weight 45 % or more but not more than 55 % of the active herbicidal ingredient Penoxsulam as an aqueous suspension
3824999248	Mixture of: — 3,3-bis(2-methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0) and — ethyl-6'-(diethylamino)-3-oxo-spiro-[isobenzofuran-1(3H),9'-[9H]xanthene]-2'-carboxylate (CAS RN 154306-60-2) 
3824999283	Preparation, consisting of two or more of the following glycols: — dipropylene glycol — tripropylene glycol — tetrapropylene glycol or — pentapropylene glycol 
3824999286, 3824999357	Liquid crystal mixture for use in the manufacture of displays (2) 

3824999383, 3824999685	Preparation containing: — C,C'-azodi(formamide) (CAS RN 123-77-3), — magnesium oxide (CAS RN 1309-48-4) and — zinc bis(p-toluene sulphinate) (CAS RN 24345-02-6) in which the gas formation from C,C'-azodi(formamide) occurs at 135 °C
3824999679	Paste containing by weight: — 75 % or more, but not more than 85 % of copper, — inorganic oxides, — ethyl cellulose, and — a solvent 
3907690050, 3926909240	Flexible packages (for oxygen sensitive polymers) manufactured from a laminate of: — not more than 75 µm of polyethylene, — not more than 50 µm of polyamide, — not more than 15 µm of polyethylene terephthalate and — not more than 9 µm of aluminium with a tensile strength of more than 70 N/15 mm and oxygen transmission rate of less than 0,1 cm <sup>3</sup> /m <sup>2</sup> /24 hrs at 0,1 MPa
3907998060	Copolymer of terephthalic acid and isophthalic acid with bisphenol A
3908900060	Copolymer consisting of: — hexanedioic acid — 12-aminododecanoic acid — hexahydro-2H-azepin-2-one, and — 1,6-hexanediamine 
3909400030	Mixture of: — alkylphenol — formaldehyde resin, whether or not brominated, and — zinc oxide 
3919108047, 3919908032	Polyester, polyurethane or polycarbonate foil: — with pressure sensitive silicone polymer adhesive, — of a total thickness of not more than 0,7 mm, — of a total width of 1 cm or more, but not more than 1 m, — whether or not in rolls of a kind used for the protection of the surface of products of headings 8521 and 8528
3919108053, 3919908034, 3920102893, 3920108950	Polyethylene foil: — with pressure sensitive, non-rubber adhesive adhering solely to clean and smooth surfaces, — of a total thickness of 0,025 mm or more, but not more than 0,7 mm, and — of a total width of 6 cm or more, but not more than 1 m, — whether or not in rolls, of a kind used for the protection of the surface of products of headings 8521 and 8528
3919908036, 3920491095	Printed laminated sheet with a central layer of poly(vinyl chloride), coated on both sides with a layer of poly(vinyl fluoride) — whether or not with a pressure or heat sensitive adhesive layer — whether or not with a release film — with a toxicity (as determined by test method ABD 0031 ) of not more than 70 ppm hydrogen fluoride, not more than 120 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together — with a flammability within 60 seconds of not more than 130 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83) — with a weight (without release film) of 240 g/m <sup>2</sup> (± 30 g/m <sup>2</sup> ) without adhesive layer, of 340 g/m <sup>2</sup> (± 40 g/m <sup>2</sup> ) with heat sensitive adhesive layer or of 330 g/m <sup>2</sup> (± 40 gm <sup>2</sup> ) with pressure sensitive layer 
3919908038	Self-adhesive film composed of: — a top layer predominantly of polyurethane mixed with acrylic polymer emulsions and titanium dioxide, — whether or not containing a second layer of a mixture of vinyl acetate-ethylene copolymer and cross-linkable vinyl acetate polymer emulsions, — not more than 6 % by weight of other additives, — a pressure sensitive adhesive; and — covered on one side with a release liner, — whether or not with a separate self-adhesive over laminate protective film, — of a total thickness of not more than 400 µm 

3919908040	Film, with a total thickness of 40 µm or more, consisting of one or more layers of transparent polyester film: — containing at least one infrared reflective layer with a total normal reflectance according to EN 12898 of 80 % or more — having on one side a layer with a normal emissivity according to EN 12898 of not more than 0,2 — coated on the other side with a pressure sensitive adhesive and a release liner
3919908042	Self-adhesive film composed of: — a first layer containing a mixture of thermoplastic polyurethane and anti-blocking agent, — a second layer containing a maleic anhydride copolymer, — a third layer containing a mixture of low density polyethylene, titanium dioxide and additives, — a fourth layer containing a mixture of low density polyethylene, titanium dioxide, additives and colour pigment, — a pressure sensitive adhesive; and — covered on one side with a release liner — whether or not with a separate self-adhesive over laminate protective film — of a total thickness of not more than 400 µm
3919908044, 3921906095	Printed laminated sheet — with a core layer of glass fabric, coated on each side with a layer of poly(vinyl chloride), — on one side covered with a layer of poly(vinyl fluoride), — whether or not with a pressure sensitive adhesive layer and a release film on the other side, — with a toxicity (as determined by test method ABD 0031 ) of not more than 50 ppm hydrogen fluoride, not more than 85 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together, — with a flammability within 60 seconds of not more than 110 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83), and — with a weight (without release film) of 490 g/m <sup>2</sup> (± 45 g/m <sup>2</sup> ) without adhesive layer or of 580 g/m <sup>2</sup> (± 50 g/m <sup>2</sup> ) with pressure sensitive layer
3919908047, 9001200040	Polariser film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side
3920104030	Co-extruded seven to nine layered film predominately of copolymers of ethylene or functionalized polymers of ethylene, consisting of: — a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers, — covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm
3920202955, 3920208093	Co-extruded seven to nine layered film predominately of copolymers of propylene, consisting of: — a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers, — covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm

3920208095	Polypropylene sheet, put up in rolls, with: — flame retardant level of UL 94 V-0 for material thicknesses of 0,25 mm or more and level UL 94 VTM-0 for material thicknesses of 0,05 mm or more but not more than 0,25 mm (as determined by Flammability Standard UL-94) — dielectric breakdown of 13,1 kV or more but not more than 60,0 kV (as determined by ASTM D149) — tensile yield in a machine direction of 30 MPa or more but not more than 33 MPa (as determined by ASTM D882) — tensile yield in a transverse direction of 22 MPa or more but not more than 25 MPa (as determined by ASTM D882) — density range of 0,988 g/cm <sup>3</sup> or more but not more than 1 035 g/cm <sup>3</sup> (as determined by ASTM D792) — moisture absorption of 0,01 % or more but not more than 0,06 % (as determined by ASTM D570) for use in the manufacture of insulators used in the electronics and electrical industries (2)
3920992855	Thermoplastic polyurethane film extruded, with: — not self-adhesive, — an index of yellow lower of more than 1,0 but not more than 2,5 for 10 mm stacked films (as determined by test method ASTM E 313-10), — a light transmission higher to 87 % for 10 mm stacked films (as determined by test method ASTM D 1003-11), — a total thickness of 0,38 mm or more, but not more than 7,6 mm, — a width of 99 cm or more, but not more than 305 cm, of a kind used in the production of laminated safety glass
5603111020, 5603119020	Non-wovens, not weighing more than 20 g/m <sup>2</sup> , containing spunbonded and meltblown filaments put together in a sandwich way with the two outer layers containing fine endless filaments (not less than 10 µm but not more than 20 µm in diameter) and the inner layer containing super-fine endless filaments (not less than 1 µm but not more than 5 µm in diameter), for the manufacture of napkins and napkin liners for babies and similar sanitary napkins (2)
6909190015	Ceramic ring with rectangular transversal section having an external diameter of 19 mm or more (+ 0,00 mm/– 0,10 mm) but not more than 29 mm (+ 0,00 mm/– 0,20 mm), an internal diameter of 10 mm or more (+ 0,00 mm/– 0,20 mm) but not more than 19 mm (+ 0,00 mm/– 0,30 mm), a thickness variable from 2 mm (± 0,10 mm) to 3,70 mm (± 0,20 mm) and heat resistance 240 °C or more, containing by weight: — 90 % (± 1,5 %) of aluminium oxide — 7 % (± 1 %) of titanium oxide
7005103010	Float glass: — of a thickness of 4,0 mm or more but not more than 4,2 mm, — with a light transmission of 91 % or more measured using a D-type light source, — coated on one surface with a fluorine doped tin dioxide reflective layer
7607209010	Aluminium laminated film of a total thickness of not more than 0,123 mm, comprising of a layer of aluminium of a thickness of not more than 0,040 mm, polyamide and polypropylene base films, and a protective coating against corrosion by hydrofluoric acid, for use in the manufacture of lithium polymer batteries (2)
7616999075	Parts in the shape of a rectangular frame: — of painted aluminium, — with a length of 1 011 mm or more but not more than 1 500 mm, — with a width of 622 mm or more but not more than 900 mm, — with a thickness of 0,6 mm (± 0,1 mm), of a kind used in the manufacture of TV sets
8105900010	Bars or wires made of cobalt alloy containing, by weight: — 35 % (± 2 %) cobalt, — 25 % (± 1 %) nickel, — 19 % (± 1 %) chromium and — 7 % (± 2 %) iron conforming to the material specifications AMS 5842 , of a kind used in the aerospace industry
8108903020	Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 00 (2)

8108905050	Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium
8504318020	Transformer for use in the manufacture of inverters in LCD modules (2) 
8505110035	Permanent magnets of an alloy of either neodymium, iron and boron, or samarium and cobalt coated having undergone inorganic passivation (inorganic coating) using zinc phosphate for the industrial manufacture of products in motor or sensory applications (2) 
8507600055	Lithium-ion accumulator or module in cylindrical form, with: — a base similar to an ellipse squeezed in the middle, — a length of 49 mm or more (not including terminals), — a width of 33,5 mm or more, — a thickness of 9,9 mm or more, — a rated capacity of 1,75 Ah or more, and — a rated voltage of 3,7 V, for the manufacture of rechargeable batteries (2) 
8507600057	Lithium-ion accumulator or module, cuboid in shape, with: — some of the corners rounded off, — a length of 76 mm or more (not including terminals), — a width of 54,5 mm or more, — a thickness of 5,2 mm or more, — a rated capacity of 3 100 mAh or more, and — a rated voltage of 3,7 V, for the manufacture of rechargeable batteries (2) 
8522908015	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and/or integrated circuits in products of heading 8521
8522908096	Hard disk drive, for incorporation in products of heading 8521 (2) 
8525801945	Camera module with a resolution of 1 280 (*1) 720 P HD, with two microphones, for use in the manufacture of products of heading 8528 (2) 
8536699081	Pitch connector for use in the manufacture of LCD television reception apparatus (2) 
8537109130	Data processing and evaluation vehicle dashboard control module, operating through the CAN — bus protocol, containing at least: — microprocessor relays, — a stepper motor, — Electrically Erasable Programmable Read-Only (EEPROM) memory, and — other passive components (such as connectors, diodes, voltage stabilizer, resistors, capacitors, transistors), with a voltage of 13,5 V
8544429030	PET insulated electric conductor with: — 10 or 80 individual wires, — a length of 50 mm or more, but not more than 800 mm, — connector(s) and/or plug(s) fitted at one or both ends, for use in the manufacture of products falling within headings 8521 and 8528 (2) 
8548909050	Filters with a ferromagnetic core, used to suppress high frequency noise in electronic circuits, for the manufacture of TV sets and monitors of heading 8528 (2) 
8704239120	Motor chassis with a self-ignition capacity of at least 8 000 cm <sup>3</sup> , fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm (2) 
9001900025	Unmounted optical elements made from moulded infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material
9001900075	Front filter comprising glass panels with special printing and film coating, for use in the manufacture of plasma display modules (2) 

9002110030	Lenses— measuring not more than 180 mm × 100 mm × 100 mm at a maximum focal length of more than 200 mm, — with a resolution of 130 lines/mm or better, and — with a zoom ratio of 18 times of a kind used for the production of visualizers or live image cameras
9002110040	Lenses— measuring not more than 125 mm × 65 mm × 65 mm, — with a resolution of 125 lines/mm or better, and — with a zoom ratio of 16 times of a kind used for the production of visualizers or live image cameras
9002110070	Lenses— measuring not more than 180 mm × 100 mm × 100 mm at a maximum focal length of more than 200 mm, — with an etendue of 7 steradian mm <sup>2</sup> or better, and — with a zoom ratio of 16 times of a kind used for the production of visualizers or live image cameras